

HPPLAM Brown HPB6

GLASS-PTFE

HPP Performance HPPSTIK HPPLAM Brown HPB6 is fiberglass fabric impregnated with PTFE (polytetrafluoroethylene) dispersion, laminated to PTFE film and coated with high-temperature, pressure-sensitive silicone adhesive.

Hi-Performance Products, Inc.
1231 Puerta Del Sol; Unit 400
San Clemente CA 92673
Customer Service: (949) 366-6088

Typical Properties

www.ptfeglass.com

Product Number	HPB6-04	HPB6-06	HPB6-10
Backing Material	PTFE-Coated Fiberglass Fabric	PTFE-Coated Fiberglass Fabric	PTFE-Coated Fiberglass Fabric
Adhesive Type	Clean Release Silicone	Clean Release Silicone	Clean Release Silicone
Total Thickness (in.)	.0063	.0079	.0114
Backing Thickness (in.)	.0043	.0059	.0094
Adhesive Thickness (in.)	.0020	.0020	.0020
Adhesion to Steel (oz./in.)	45	50	55
Elongation (% at break)	<5	<5	<5
Operating Temperature (°F)	-100 to 500	-100 to 500	-100 to 500
Color	Brown	Brown	Brown

Values shown are typical. Certified test reports for writing specifications are available.

Applications—HPP Performance Brown HPB6 is frequently used by the packaging industry as a release surface on heat sealers, blister formation and form-fill equipment where heavy production demands a product with more release surface material. The durability and anti-stick properties of HPB6 also make it an ideal material for the lining of guide rails, chutes and slides. The high temperature capabilities and non-stick properties of HPB6 allow it to perform as an excellent release surface in severe industrial environments, platen covers, dry can covers and the composite aircraft industry.

Features/Benefits—HPB6 is a laminate construction offering an additional 0.001" (1 mil) of PTFE over the entire surface of the impregnated cloth. This makes an even more durable and

longer lasting product than our standard SGXX tapes. The combination of uniform and pin-hole-free film enables HPPLAM Brown Tapes to outperform thicker, higher grade PTFE-coated fiberglass tapes at similar prices. HPB6 is dimensionally stable and resistant to tears, punctures, abrasion and wear.

Availability—HPB6 is available in 4,6 and 10 mil thicknesses and widths from 1/4" to 37" wide. Standard roll length is 18 or 36 yards long. HPB6 is available with or without a liner.

Limited Warranty:

For a period of 6 months from the date of first sale, Hi-Performance Products, Inc. warrants this product(s) to be free from defects in manufacturing. Our only obligation will be to provide replacement product for any portion proving defective, or at our option, to refund the purchase price thereof. User assumes all other risks, if any, including the risk of injury, loss or damage, whether direct or consequential, arising out of the use, misuse, or inability to use this product(s). Hi-Performance Products, Inc. DISCLAIMS ANY AND ALL OTHER WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

NOTE:

HPP, Inc. does not assume any responsibility or liability for any advice furnished by it, or for the performance or results of any installation or use of the product(s) or of any final product into which the product(s) may be incorporated by the purchaser and/or user. The purchaser and/or user should perform its own tests to determine the suitability and fitness of the product(s) for the particular purpose desired in any given situation.