

HP03015

HP 03015 is a flame-retardant (UL 94 HB) silicone rubber coated fiberglass fabric with an operating temperature range of -85°F to +500°F. Typical applications include heater covering, shrink tunnel curtains, cable wraps, release or separator fabrics.

Typical Physical Properties*

Property	Units	Value
Weight	Oz./Yd.2 Avg.	14
Overall Thickness	Inches	0.014
Tensile Strength (Warp)	Lbs./In.	250
Tensile Strength (Fill)	Lbs./In.	200
Elongation	%	<10
Temperature Range		-85°F - +500°F
Color		Black
UL	(94)	HB

*Values are typical properties and should not be used for writing specifications.

Availability

HP03015 is sold by the yard in continuous lengths, 40" wide. Please contact customer service for minimum order quantities, price and delivery.

Custom product. Contact Customer Service for minimum order, price and delivery.

Application Advantages

- Combination of silicone coating and fiberglass is flexible and compressible.
- Resistant to wear and tear.
- Excellent low temperature resistance -85°F.

Hi-Performance Products, INC.
1231 Puerta Del Sol, Unit 400
San Clemente CA 92673
Customer Service: (949)366-6088

ptfglass.com

Limited Warranty: For a period of 6 months from the date of first sale, Hi-Performance Products warrants this product(s) to be free from defects in manufacturing. Our only obligation will be to provide replacement product for any portion proving defective, or at our option, to refund the purchase price thereof. User assumes all other risks, if any, including the risk of injury, loss or damage, whether direct or consequential, arising out of the use, misuse, or inability to use this product(s). Hi-Performance Products **DISCLAIMS ANY AND ALL OTHER WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.**

NOTE: Hi-Performance Products does not assume any responsibility or liability for any, advice furnished, by it, or for the performance, or results of any installation or use of the product(s) or of any final product into which the product(s) may be incorporated by the purchaser and / or user. The purchaser and/or user should perform its own tests to determine the suitability and fitness of the product(s) for the particular purpose desired in any given situation.