

weave construction is designed for critical belting applications requiring good tracking and minimal elongation of the belt.

[www.ptfeglass.com](http://www.ptfeglass.com)

## Typical Physical Properties

Property	Units	Value
Substrate		Fiberglass
Coating Material		PTFE
Widths Available	Inches	62
Weight	Oz./Yd. <sup>2</sup>	21.0
Thickness	Inches	0.024
Breaking Strength (Warp)	Lbs./In.	600
Breaking Strength (Fill)	Lbs./In.	450
Trapezoidal Tear (Warp)	Lbs.	60
Trapezoidal Tear (Fill)	Lbs.	40
Porosity	SCFM/Ft. <sup>2</sup>	>5
Elongation at 40 lbs./in.	%	1.0 Maximum

The data listed above is for reference only. It is not intended for use as a guarantee of product performance.

### Limited Warranty:

For a period of 6 months from the sale, Hi-Performance Products, Inc. warrants this product(s) to be free from defects in material and manufacturing. Our only obligation is to provide replacement product for a portion proving defective, or at our option to refund the purchase price therefor. Buyer assumes all other risks, if any, including the risk of injury, loss or damage, whether or not consequential, arising out of the use, misuse, or inability to use this product. Hi-Performance Products, Inc. DISCLAIMS ANY AND ALL OTHER WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

### NOTE:

HPP, Inc. does not assume any responsibility or liability for any accident or injury furnished by it, or for the performance or results of any installation or use of the product(s) or of any final product incorporating the product(s) may be incorporated into the purchaser and/or user. The purchaser and user should perform its own tests to determine the suitability and fitness of the product(s) for the particular purpose in any given situation.