

# HP27300

## FILM-UHMW

HPP Performance HPPSTIK HP27300 is manufactured from UHMW (Ultra High Molecular Weight) polyolefin film coated with rubber adhesive.

High Performance Products  
1231 Puerta Del Sol; Unit 400  
San Clemente CA 92673  
Customer Service: (949) 366-6088

### Typical Properties

[www.ptfglass.com](http://www.ptfglass.com)

Product Number	HP27300-5R	HP27300-10R
Backing Material	Film-UHMW	Film-UHMW
Adhesive Type	Thermosetting Rubber	Thermosetting Rubber
Total Thickness (in.)	.0070	.0120
Backing Thickness (in.)	.0050	.0100
Adhesive Thickness (in.)	.0020	.0020
Adhesion to Steel (oz./in.)	55	55
Tensile Strength (lbs./in.)	40	80
Elongation (% at break)	350	400
Taber Abrasion Resistance (Mg.)	0.4 Max. @ 1000 gm. Load & 1000 Revolutions	0.4 Max. @ 1000 gm. Load & 1000 Revolutions
Coefficient of Kinetic Friction	0.11-0.25	0.11-0.25
Operating Temperature (°F)	-40 to 225	-40 to 225
Color	Natural	Natural

Limited Warranty: For a period of 6 months from the date of first sale, High Performance Products warrants this product(s) to be free from defects in manufacturing. Our only obligation will be to provide replacement product for any portion proving defective, or at our option, to refund the purchase price thereof. User assumes all other risks, if any, including the risk of injury, loss or damage, whether direct or consequential, arising out of the use, misuse, or inability to use this product(s). High Performance Products  
DISCLAIMS ANY AND ALL OTHER WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

NOTE: High Performance Products does not assume any:

Values shown are typical. Certified test reports for writing specifications are available.

Applications—HP27300 tapes can be used to provide an abrasion-resistant, anti-stick, anti-friction surface at temperatures up to 225°F. HP27300 is frequently used to line chutes and conveyors.

HP27300 is often applied to guide rails to reduce noise levels in glass bottling plants. This tape is also used to replace desk drawer bearings to provide silky smooth, friction-free drawer movement.

Features/Benefits—HP27300 exhibits excellent abrasion resistance and it has a low coefficient of friction, making it an excellent protection for surfaces or bearings that experience heavy wear. HP27300 is more economical than PTFE tapes.

The high-temperature, high-tack rubber adhesive adheres readily to most dry, clean surfaces—firmly anchoring the product in place.

Availability—HP27300 is available in 5 and 10 mil thicknesses. Factory stock for HP27300 is in master rolls 36 yards by 24". Rolls can be slit in widths from 1/4" to 24". This product is supplied with a film inter-liner, which protects the adhesive, facilitates die cutting and peels off easily.

responsibility or liability for any advice furnished by it, or for the performance or results of any installation or use of the product(s) or of any final product into which the product(s) may be incorporated by the purchaser and/or user. The purchaser and/or user should perform its own tests to determine the suitability and fitness of the product(s) for the particular purpose desired in any given situation.