

HPPLAM Series

HPPLAM Laminates . . . Layers above the rest!

The HPPLAM series is the HPPLAM value line of industrial laminates.

Features

PTFE cast barrier film surface, crack and pinhole free

Uniform film thickness over entire surface

High temperature fabrics

FDA Compliant

Benefits

Outperforms simple PTFE-coated materials; long-lasting release properties make cleaning easier; low wicking properties extend useful life

Lamination eliminates the possibility of thin spots found in coated materials, which often lead to their premature failure

Designed for thermal cycling and harsh chemical applications, including cooking and plastic processing

Suitable for use in direct food contact applications under the applicable requirements of 21CFR177.1550

Typical Properties¹

Product Number	HPPLAM 100	HPPLAM 200	HPPLAM 300
Nominal Width ² (in.)	37.5,49 ³	37.5 ³ ,43.5 ³ ,49 ³	37.5,43 ³ ,49
Weight Nominal (oz./yd. ²)	5.6	8.8	13.4
Thickness Nominal (in.)	0.0042	0.0058	0.0095
Breaking Strength (lbs./in.)	90 X 70	120 X 120	315 X 215
Tear Strength (lbs.)	3.0 X 2.0	5.0 X 4.5	18.0 X 12.0
Color	Brown/Brown	Brown/Brown	Brown/Brown

Hi-Performance Products, INC.
1231 Puerta Del Sol, Unit 400
San Clemente CA 92673
Customer Service: (949)366-6088

ptfeglass.com

Limited Warranty: For a period of 6 months from the date of first sale, Hi-Performance Products warrants this product(s) to be free from defects in manufacturing. Our only obligation will be to provide replacement product for any portion proving defective, or at our option, to refund the purchase price thereof. User assumes all other risks, if any, including the risk of injury, loss or damage, whether direct or consequential, arising out of the use, misuse, or inability to use this product(s). Hi-Performance Products **DISCLAIMS ANY AND ALL OTHER WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.**

NOTE: Hi-Performance Products does not assume any responsibility or liability for any, advice furnished, by it, or for the performance, or results of any installation or use of the product(s) or of any final product into which the product(s) may be incorporated by the purchaser and / or user. The purchaser and/or user should perform its own tests to determine the suitability and fitness of the product(s) for the particular purpose desired in any given situation.

1- Properties representative of actual test data. Not to be used for specification purposes. 2- Nominal width. Minimum usable width may be as much as one inch less than nominal. 3- Special order, minimum quantities may apply. Other widths available on request.