

KCF1589 is an open mesh plain weave belting material, which is frequently used for light duty belting applications.

Typical Physical Properties

Property	Units	Value
Substrate (Warp) (Fill)		KEVLAR® Fiberglass
Coating Material		PTFE
Widths Available	Inches	80" MAX
Weight	Oz./Yd. ²	6.2 – 7.2
Thickness	Inches	015
Breaking Strength (Warp)	Lbs./In.	350
Breaking Strength (Fill)	Lbs./In.	350
Porosity	SCFM/Ft. ²	750
Elongation at 40 lbs./in.	%	0.4

The data listed above is for reference only. It is not intended for use as a guarantee of product performance.

KCF1589

Hi-Performance Products, Inc.
1231 Puerta Del Sol; Unit 400
San Clemente CA 92673
Customer Service: (949) 366-6088

www.ptfeglass.com

Limited Warranty:

For a period of 6 months from the date of first sale, Hi-Performance Products, Inc. warrants this product(s) to be free from defects in manufacturing. Our only obligation will be to provide replacement product for any portion proving defective, or at our option, to refund the purchase price thereof. User assumes all other risks, if any, including the risk of injury, loss or damage, whether direct or consequential, arising out of the use, misuse, or inability to use this product(s). Hi-Performance Products, Inc. DISCLAIMS ANY AND ALL OTHER WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

NOTE:

HPP, Inc. does not assume any responsibility or liability for any advice furnished by it, or for the performance or results of any installation or use of the product(s) or of any final product into which the product(s) may be incorporated by the purchaser and/or user. The purchaser and/or user should perform its own tests to determine the suitability and fitness of the product(s) for the particular purpose desired in any given situation.